

1

2

3

4

5

6

A

B

C

D

Installation Example
Pavement Class B 125

3-5 mm durable overhang

pavement / Flagstone

bedding course

base course

load bearing structure according to standard

x, y, z

* y ≥ Channel height - 6 cm

Category according to EN 1433 / DIN 19580		A 15	B 125	C 250	D 400**	E 600	F 900	Applying to following systems:		
Foundation: width x / height y / thickness z (in cm)			10 / * / 6					DRIVETEC PA / ST/ ME 100		
EN 206-1 / DIN 1045-2	quality of concrete stretcher									
The named concrete quality is a minimum quality	without danger of frost on the lateral support		C25/30 X0							
	with danger of frost on the lateral support		C25/30 XF3							
<div><div>The installation examples / advise constantly are adapted to the technical conditions. With new editions older expenditures lose their validity. Before planning or installation please verify the current version at www.hauraton.com In building construction is a sealing layer below the channels necessary.</div><div>The installation example represents a proven recommendation of the HAURATON company. The final responsibility for the design of e.g. expansion joints or the suitable load transfer is with the responsible planner, the responsibility for the execution is with the contractor.</div></div>				Date: 15.10.2024		Our general installation instructions apply.		Format DIN	A4	<div><div></div><div>Unit 4, Frenchs Avenue LU6 1BH Dunstable / Bedfordshire United Kingdom</div><div>Tel. +44 1582 501380 TS-UK@hauraton.com</div></div>
								scale	1:5	
				0000151215_BRITISH.dwg		8		EBBw		
				DRIVETEC-PA/ST/ME-100 Rinnenunterteil Einbaubeispiel Klasse B 125 in Pflaster						

1

2

3

4

5

6

A

B

C

D

1

2

3

4

5

6

A

B

C

D

Installation Example
Pavement Class B 125

3-5 mm durable overhang

pavement / Flagstone

bedding course

base course

load bearing structure according to standard

x, y, z

* y ≥ Channel height - 6 cm

Category according to EN 1433 / DIN 19580		A 15	B 125	C 250	D 400**	E 600	F 900	Applying to following systems:	
Foundation: width x / height y / thickness z (in cm)			10 / * / 6					DRIVETEC PA / ST/ ME 100	
EN 206-1 / DIN 1045-2	quality of concrete stretcher								
	without danger of frost on the lateral support		C25/30 X0						
	with danger of frost on the lateral support		C25/30 XF3						
The installation examples / advise constantly are adapted to the technical conditions. With new editions older expenditures lose their validity. Before planning or installation please verify the current version at www.hauraton.com In building construction is a sealing layer below the channels necessary.				Date: 15.10.2024		Our general installation instructions apply.		Format DIN A4	 Unit 4, Frenchs Avenue LU6 1BH Dunstable / Bedfordshire United Kingdom Tel. +44 1582 501380 TS-UK@hauraton.com
The installation example represents a proven recommendation of the HAURATON company. The final responsibility for the design of e.g. expansion joints or the suitable load transfer is with the responsible planner, the responsibility for the execution is with the contractor.				0000151215_BRITISH.dwg 8		EBBw	scale 1:5		
				DRIVETEC-PA/ST/ME-100 Rinnenunterteil Einbaubeispiel Klasse B 125 in Pflaster					

1

2

3

4

5

6

A

B

C

D

Installation Example
Pavement Class B 125

3-5 mm durable overhang

pavement / Flagstone

bedding course

base course

load bearing structure according to standard

x, y, z

* y ≥ Channel height - 6 cm

Category according to EN 1433 / DIN 19580		A 15	B 125	C 250	D 400**	E 600	F 900	Applying to following systems: DRIVETEC PA / ST/ ME 100	
Foundation: width x / height y / thickness z (in cm)			10 / * / 6						
EN 206-1 / DIN 1045-2	quality of concrete stretcher								
The named concrete quality is a minimum quality	without danger of frost on the lateral support		C25/30 X0						
	with danger of frost on the lateral support		C25/30 XF3						
<div><div>The installation examples / advise constantly are adapted to the technical conditions. With new editions older expenditures lose their validity. Before planning or installation please verify the current version at www.hauraton.com In building construction is a sealing layer below the channels necessary.</div><div>The installation example represents a proven recommendation of the HAURATON company. The final responsibility for the design of e.g. expansion joints or the suitable load transfer is with the responsible planner, the responsibility for the execution is with the contractor.</div></div>				Date: 15.10.2024		Our general installation instructions apply.		Format DIN	A4
								scale	1:5
				0000151215_BRITISH.dwg		8	EBBw	<div><div></div><div>Unit 4, Frenchs Avenue LU6 1BH Dunstable / Bedfordshire United Kingdom</div><div>Tel. +44 1582 501380 TS-UK@hauraton.com</div></div>	
				DRIVETEC-PA/ST/ME-100 Rinnenunterteil Einbaubeispiel Klasse B 125 in Pflaster					